

Certification
Issued Under the Authority of the
Federal Communications Commission
By:

KL-Certification GmbH
Heinrich-Hertz-Allee 7
St. Ingbert, 66386
Germany

Date of Grant: 11/19/2025
Application Dated: 11/19/2025

M5Stack Technology Co.,Ltd
Block A10, Expo Bay South Coast,
Fuhai Street, Bao'an District,
Shenzhen,Guangdong,
China

Attention: Jimmy Lai ,

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is
VALID ONLY for the equipment identified hereon for use under the Commission's
Rules and Regulations listed below.

FCC IDENTIFIER: 2AN3WM5STAMPC6LORA
Name of Grantee: M5Stack Technology Co.,Ltd
Equipment Class: Digital Transmission System
Notes: M5Stamp C6LORA
Modular Type: Single Modular

<u>Grant Notes</u>	<u>FCC Rule Parts</u>	<u>Frequency Range (MHZ)</u>	<u>Output Watts</u>	<u>Frequency Tolerance</u>	<u>Emission Designator</u>
	15C	903.0 - 914.2	0.0018		
	15C	2402.0 - 2480.0	0.0013		
	15C	2412.0 - 2462.0	0.0272		

Single Modular Approval. Output power listed is peak conducted. Grantee is responsible for providing specific testing instructions to host manufacturers for additional testing to verify compliance as a composite system. This includes retesting of transmitter module per part 15.31(h) and (k) and verification of compliance with FCC RF Exposure requirements. This module is restricted to installation in products for use only in mobile and fixed applications. Separate approval is required for all other operating configurations, including portable configurations with respect to 2.1093. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20cm from all persons. OEM integrators and end-users must be provided with transmitter operation conditions for satisfying RF exposure compliance. This device supports 802.11b, 802.11g and 802.11n with a 20 MHz and 40 MHz bandwidth mode.